

**Voltage Range:** 12/24V

**Warranty:** 5 years

**Ingress Protection:** IP67

**Approval:** ECE & EMC ✓

- 80mm square lamp modules
- Quad surface mounting bracket
- Tough polycarbonate lenses
- Shock, water & dust proof

- Replacement lamp modules available; 80AMEB, 80RMEB, 80WMEB, 80FMEB
- Harness system compatible (80BFWARME only)



**STOP / TAIL / INDICATOR / REVERSE**

**80BRRAWME**

Current Draw (13.8V / 28V):  
 Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A,  
 Reverse: 0.17A / 0.21A



**STOP / TAIL / INDICATOR / FOG**

**80BFARRME**

Current Draw (13.8V / 28V):  
 Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A,  
 Fog: 0.42A / 0.21A



**STOP / TAIL / INDICATOR / REVERSE / FOG**

**80BFWARME**

Current Draw (13.8V / 28V):  
 Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A,  
 Reverse: 0.17A / 0.21A, Fog: 0.42A / 0.21A



**STOP / TAIL / INDICATOR**

**80BAARRME**

Current Draw (13.8V / 28V):  
 Stop: 0.33A / 0.25A, Tail: 0.06A / 0.04A, Indicator: 0.29A / 0.22A

